



# The world’s hardest-working forklifts


When you buy a Konecranes forklift, you are investing in time-tested technology with innovative, eco-efficient features to enhance productivity and cut lifecycle costs. We offer a range of solutions and technologies to reduce engine, drive train

and tire wear, extend the functional life of your forklift and decrease your running expenses. When your lifting needs change, a well-maintained forklift also has high resale value.



## 10–18 Tons

| MODEL NAME     | CAPACITY            | WHEELBASE |
|----------------|---------------------|-----------|
| SMV 10–600 CS  | 10 tons at 600 mm   | 2800 mm   |
| SMV 12–600 CS  | 12 tons at 600 mm   | 3000 mm   |
| SMV 10–600 C   | 10 tons at 600 mm   | 3000 mm   |
| SMV 12–600 C   | 12 tons at 600 mm   | 3000 mm   |
| SMV 10–1200 C  | 10 tons at 1200 mm  | 3250 mm   |
| SMV 13.6–600 C | 13.6 tons at 600 mm | 3250 mm   |
| SMV 12–1200 C  | 12 tons at 1200 mm  | 3500 mm   |
| SMV 16–600 C   | 16 tons at 600 mm   | 3500 mm   |
| SMV 16–900 C   | 16 tons at 900 mm   | 3500 mm   |
| SMV 15–1200 C  | 15 tons at 1200 mm  | 3750 mm   |
| SMV 16–1200 C  | 16 tons at 1200 mm  | 3750 mm   |
| SMV 18–600 C   | 18 tons at 600 mm   | 3750 mm   |
| SMV 18–900 C   | 18 tons at 900 mm   | 3750 mm   |



## 18–33 Tons

| MODEL NAME      | CAPACITY             | WHEELBASE |
|-----------------|----------------------|-----------|
| SMV 18–1200 CS  | 18 tons at 1200 mm   | 4000 mm   |
| SMV 20–1200 CS  | 20 tons at 1200 mm   | 4000 mm   |
| SMV 22–1200 C   | 22 tons at 1200 mm   | 4250 mm   |
| SMV 23.6–1200 C | 23.6 tons at 1200 mm | 4250 mm   |
| SMV 25–1200 C   | 25 tons at 1200 mm   | 4250 mm   |
| SMV 28–1200 C   | 28 tons at 1200 mm   | 4500 mm   |
| SMV 32–1200 C   | 32 tons at 1200 mm   | 4750 mm   |
| SMV 33–1200 C   | 33 tons at 1200 mm   | 4750 mm   |

Other models upon request



## 37–65 Tons

| MODEL NAME    | CAPACITY           | WHEELBASE |
|---------------|--------------------|-----------|
| SMV 37–1200 C | 37 tons at 1200 mm | 5000 mm   |
| SMV 42–1200 C | 42 tons at 1200 mm | 5500 mm   |
| SMV 45–1200 C | 45 tons at 1200 mm | 5500 mm   |
| SMV 50–1200 C | 50 tons at 1200 mm | 6000 mm   |
| SMV 52–1200 C | 52 tons at 1200 mm | 6000 mm   |
| SMV 55–1200 C | 55 tons at 1200 mm | 6000 mm   |
| SMV 60–1200 C | 60 tons at 1500 mm | 6000 mm   |
| SMV 65–1200 C | 65 tons at 1200 mm | 6000 mm   |



## E-VER 10–25 Tons

| MODEL NAME       | CAPACITY            | WHEELBASE |
|------------------|---------------------|-----------|
| E-VER 10–600 C   | 10 tons at 600 mm   | 3000 mm   |
| E-VER 12–600 C   | 12 tons at 600 mm   | 3000 mm   |
| E-VER 10–1200 C  | 10 tons at 1200 mm  | 3250 mm   |
| E-VER 13.6–600 C | 13.6 tons at 600 mm | 3250 mm   |
| E-VER 12–1200 C  | 12 tons at 1200 mm  | 3500 mm   |
| E-VER 16–600 C   | 16 tons at 600 mm   | 3500 mm   |
| E-VER 16–900 C   | 16 tons at 900 mm   | 3500 mm   |
| E-VER 15–1200 C  | 15 tons at 1200 mm  | 3750 mm   |
| E-VER 16–1200 C  | 16 tons at 1200 mm  | 3750 mm   |
| E-VER 17–1200 C  | 17 tons at 1200 mm  | 3750 mm   |
| E-VER 18–600 C   | 18 tons at 600 mm   | 3750 mm   |
| E-VER 18–900 C   | 18 tons at 900 mm   | 3750 mm   |
| E-VER 18–1200 C  | 18 tons at 1200 mm  | 4000 mm   |
| E-VER 20–1200 C  | 20 tons at 1200 mm  | 4000 mm   |
| E-VER 22–1200 C  | 22 tons at 1200 mm  | 4250 mm   |
| E-VER 25–1200 C  | 25 tons at 1200 mm  | 4250 mm   |